

Product Name PBO fiber ZYLON

First issue : Aug. 10, 2000 Revised : May. 17, 2016

MSDS No. 00160F

MATERIAL SAFETY DATA SHEET

1 PRODUCT AND COMPANY IDENTIFICATION

Product Name PBO fiber ZYLON®

SUPPLIER

Name TOYOBO Co., Ltd.

Address 2-8 Dojima Hama 2-chome, Kita-Ku

OSAKA 530-8230 JAPAN

Telephone No. +81-6-6348-3130 Fax No. +81-6-6348-3413

Recommended use Woven fabric, Knitted fabric, Felt, Rope&Cable, FRP, FRR, etc

Restrictions on use Medical product

2 HAZARDS IDENTIFICATION

Most Important Hazards Few adverse human health effects are anticipated.

Specific Hazards Since it is high strength, the fiber can severely cut fingers or skin.

Decomposes and emits toxic fumes at higher than 600°C.

GHS Classification Not classified

3 COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Product Article

(substance/mixture)

Chemical Name Poly[Benz(1,2-D:5,4-D')bisoxazole-2,6-diyl-1,4-phenylen]
Synonym 1,4-benzenedicarboxylic acid, polymer with 4,6-diamino-1, 3-

benzenediol dihydrochloride

CAS No. 60857-81-0

Components Contributing to

the Hazard

Substances classified as hazardous are less than 0.1%.

GHS Classification Not classified

4 FIRST-AID MEASURES

Inhalation Remove to fresh air if effect occurs. Consult a physician.

Skin Contact Wash off in running water or shower.

Eye Contact Flush eyes with plenty of water. If irritation persists, seek

medical attention.

Ingestion Induce vomiting. If indisposition continues, seek medical

attention.

5 FIRE-FIGHTING MEASURES

Extinguishing Media Water, Foam, Dry Chemical

Specific Hazards Decomposes and emits toxic fumes such as hydrogen cyanide

under fire or in environments above 600°C.

Protection of Firefighters Wear self-contained breathing apparatus and protective clothing

at large scale fires.

6 ACCIDENTAL RELEASE MEASURES

Personal Precautions Can severely cut or even sever fingers when entangled.

Environmental Precautions May entangle and injure wild animals.

Methods for Cleaning up Sweep up with a vacuum cleaner or a broom.



Product Name PBO fiber ZYLON First issue: Aug. 10, 2000

Revised: May. 17, 2016

MSDS No. 00160F

MATERIAL SAFETY DATA SHEET

7 HANDLING AND STORAGE

HANDLING

Technical Measures When cutting or handling short fibers, minimize the generation of

fine fibrils. When fine fibrils are being generated, use with a local

exhaust system.

To avoid damage to equipment or injury to personnel, equipment

used to process high strength fiber should have fail-safe

mechanisms in case of entanglement.

Precautions Good ventilation is needed at work area. If dust exposure causes

eye discomfort, use chemical goggles.

Safe Handling Advice Since high strength fiber can severely cut or even sever fingers,

avoid touching a moving thread line. Avoid entanglement in a

moving thread line as bodily injury may result.

STORAGE

Technical Measures No special measures needed.

Storage Conditions To maintain the mechanical properties, the fiber is to be stored

free from exposure to light, high temperature and humidity.

Incompatible Products None

Packaging Materials To maintain the mechanical properties, store in light-proof

package.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING MEASURES Good ventilation should be sufficient for most conditions. A local

exhaust system may be necessary for some operations.

PERSONAL PROTECTIVE EQUIPMENT

Respiratory Protection When cutting or mechanically working this material, wear an

approved high-efficiency particulate respirator.

Hand Protection In order to prevent skin-abrasion or friction-burn, put on heat-

resistant gloves.

Eye Protection Use safety glasses. If dust exposure causes eye discomfort, use

chemical goggles.

Skin and Body Protection In order to prevent skin-abrasion or friction-burn, protective

clothing should be worn.

9 PHYSICAL AND CHEMICAL PROPERTIES

Physical State Solid (long fibers)

Color Golden yellow to reddish brown

Odor None

pH Not applicable
Boiling Point Not applicable
Melting Point Not applicable
Decomposition Temperature 600° C and above
Flash Point 600° C and above

Explosion Temperature None at ambient temperature

Density $1.54 \text{ to } 1.56 \text{ g/cm}^3$

Solubility Insoluble in Water. Partially soluble in aqueous strong acid.



Product Name PBO fiber ZYLON

First issue : Aug. 10, 2000 Revised : May. 17, 2016

MSDS No. 00160F

MATERIAL SAFETY DATA SHEET

10 STABILITY AND REACTIVITY

Stability Stable Possible Hazardous Reactions None

Conditions to Avoid Avoid open fire, heated environment at over 600°C.

Hazardous Decomposition Hydrogen cyanide during incineration.

Products

11 TOXICOLOGICAL INFORMATION

Acute Toxicity Not available

Local Effects

Inhalation Fibrils could be inhaled and may cause respiratory irritation.

Skin Contact Fibers may cause slight irritation especially at clothing binding

points.

Eye Contact Could cause mechanical irritation upon eye contact.

Subchronic Toxicity Data on other types of fibers suggest that repeated excessive

inhalation exposures to air borne fibrils may cause respiratory

irritation and lung effects / injury.

Specific Effects

Carcinogenicity Lung injury and tumors have been observed in laboratory animals

exposed to respirable fibrils of another structurally similar

material for two years.

Mutagenicity Negative

12 ECOLOGICAL INFORMATION

Mobility Unlikely to move in environment.

Persistence/Degradability Persists for a long time in the environment.

Bioaccumulation Unlikely to occur.

13 DISPOSAL CONSIDERATIONS

Waste from Residues Dispose of in accordance with all applicable local and national

laws and regulations.

Contaminated Packaging Dispose in the same way as the material.

14 TRANSPORTATION INFORMATION

International Regulations

UN Classification Number Not classified

Follow all of the laws and regulations in your country

Specific Precautions Do not drop, overturn, or destroy containers for heavy load.

To prevent packages from breaking, keep dry and handle with

care.

15 REGULATORY INFORMATION

Follow all of the laws and regulations in your country.

16 OTHER INFORMATION

Notice The information in this MSDS, to the best of our knowledge, is

accurate and correct. However, TOYOBO makes no warranty and assumes no liability whatsoever in connection with any use of this information. The MSDS is subject to revision as new information

becomes available.